

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ARC Polymer Composite. Repair damage caused by impact, abrasion, erosion or corrosion; rebuild worn areas; fill holes and cracks; provide abrasion resistant surfaces.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	D-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin Irrit. 2; H315
Eye Irrit. 2; H319
Skin Sens. 1; H317
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane 2,2'-[({1-Methylethyliden)bis(4,1-phenyleneoxymethylen)}]bisoxiran
Quartz - Crystalline Silica

Signal word: Warning

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 2 of 17

Pictograms:



Hazard statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H317	May cause an allergic skin reaction.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313	If eye irritation persists: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P391	Collect spillage.
P501	Dispose of contents/container to an appropriate recycling or disposal facility.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 3 of 17

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			15 - < 20 %
	701-263-0		01-2119454392-40	
	Skin Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H317 H411			
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran			10 - < 15 %
	216-823-5	603-073-00-2	01-2119456619-26	
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, Aquatic Chronic 2; H315 H319 H317 H411			
13463-67-7	titanium dioxide			1 - < 5 %
	236-675-5	022-006-00-2	01-2119489379-17	
	Carc. 2; H351			
14808-60-7	Quartz - Crystalline Silica			1 - < 5 %
	238-878-4			
	STOT RE 1; H372			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
9003-36-5	701-263-0	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	15 - < 20 %
	dermal: LD50 = > 2000 mg/kg; oral: LD50 = > 5000 mg/kg		
1675-54-3	216-823-5	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran	10 - < 15 %
	inhalation: LC50 = ca. 24,6 mg/l (vapours); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 19800 mg/kg Skin Irrit. 2; H315: >= 5 - 100 Eye Irrit. 2; H319: >= 5 - 100		
13463-67-7	236-675-5	titanium dioxide	1 - < 5 %
	oral: LD50 = > 2000 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Change contaminated, saturated clothing. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 4 of 17

respiration.

Remove person to fresh air and keep comfortable for breathing.

After contact with skin

Take off contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Seek medical advice immediately.

After contact with eyes

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

Remove contact lenses, if present and easy to do. Continue rinsing.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Let 1 glass of water be drunk in little sips (dilution effect).

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Causes eye irritation.

Causes skin irritation.

4.3. Indication of any immediate medical attention and special treatment needed

First Aid, decontamination, treatment of symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO₂)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

- Carbon monoxide
- Carbon dioxide
- Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Special protective equipment for firefighters Protective clothing. In case of fire: Wear self-contained breathing apparatus.

Co-ordinate fire-fighting measures to the fire surroundings.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 5 of 17

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- Remove persons to safety.
- Provide adequate ventilation.
- Safe handling: see section 7
- Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

- Safe handling: see section 7
- Personal protection equipment: see section 8
- Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

- Wear personal protection equipment (refer to section 8).
- Keep container tightly closed.
- Take off contaminated clothing and wash it before reuse.

Advice on protection against fire and explosion

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

Advice on general occupational hygiene

- Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.
- Use protective skin cream before handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Hints on joint storage

- Keep away from:
 - Food and feedingstuffs
 - Oxidising agent

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 6 of 17

Further information on storage conditions

Keep away from:

- Frost
- Heat
- Humidity

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

CAS No	Substance	ppm	mg/m ³	fib/cm ³	Category	Origin
14808-60-7	Quartz, respirable dust (crystalline silica)	-	0.1		TWA (8 h)	
409-21-2	Silicon carbide, respirable dust	-	3		TWA (8 h)	
13463-67-7	Titanium dioxide, respirable dust	-	4		TWA (8 h)	

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 7 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
409-21-2	Silicon carbide			
	Worker DNEL, acute	inhalation	systemic	94 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	23 mg/m ³
	Consumer DNEL, acute	dermal	systemic	200 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	13 mg/kg bw/day
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane			
	Worker DNEL, long-term	inhalation	systemic	29,39 mg/m ³
	Worker DNEL, long-term	dermal	systemic	104,15 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	0,0083 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	8,7 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	62,5 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	6,25 mg/kg bw/day
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran			
	Worker DNEL, long-term	inhalation	local	310 mg/m ³
	Consumer DNEL, long-term	inhalation	local	55 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	4,93 mg/m ³
	Worker DNEL, long-term	dermal	systemic	0,75 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,87 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	0,0893 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,5 mg/kg bw/day
13463-67-7	titanium dioxide			
	Worker DNEL, long-term	inhalation	local	1,25 mg/m ³
	Consumer DNEL, long-term	oral	systemic	700 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 8 of 17

PNEC values

CAS No	Substance	Value
Environmental compartment		Value
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	
Freshwater		0,003 mg/l
Freshwater (intermittent releases)		0,025 mg/l
Marine water		0 mg/l
Freshwater sediment		0,294 mg/kg
Marine sediment		0,029 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,237 mg/kg
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran	
Freshwater		0,006 mg/l
Freshwater (intermittent releases)		0,018 mg/l
Marine water		0,001 mg/l
Freshwater sediment		0,341 mg/kg
Marine sediment		0,034 mg/kg
Secondary poisoning		11 mg/kg
Micro-organisms in sewage treatment plants (STP)		10 mg/l
Soil		0,065 mg/kg

8.2. Exposure controls

Appropriate engineering controls

No special measures are necessary.

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

- Eye glasses with side protection
- goggles

Hand protection

Tested protective gloves must be worn: EN ISO 374

NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)

Thickness of the glove material \geq 0,4 mm

Breakthrough times and swelling properties of the material must be taken into consideration.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 9 of 17

Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))

Observe the wear time limits as specified by the manufacturer.

Skin protection

For the protection against direct skin contact, body protective clothing is essential (in addition to the usual working clothes).

Respiratory protection

Usually no personal respirative protection necessary.

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.

Combination filtering device A-P2

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Liquid
Colour: black or grey

	Test method
Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	No data available
Flammability	
Solid/liquid:	No data available
Gas:	No data available
Lower explosion limits:	No data available
Upper explosion limits:	not applicable
Flash point:	249 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	not applicable
Water solubility:	No data available
Solubility in other solvents	
No information available.	
Partition coefficient n-octanol/water:	No data available
Vapour pressure:	No data available
Density:	1,9 - 2 g/cm ³
Relative vapour density:	>1 (air = 1)

9.2. Other information

Information with regard to physical hazard classes

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 10 of 17

Explosive properties

not explosive according to EU A.14

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

Not oxidising.

Other safety characteristics

Evaporation rate:

<1 (Ether = 1)

Viscosity / dynamic:

700k mPa·s

(at 25 °C)

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

The substance is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Heat > 149 °C

10.5. Incompatible materials

- Strong alkali,
- Strong acid,
- Oxidising agent

10.6. Hazardous decomposition products

- Carbon monoxide,
- aldehydes,
- Acid

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 11 of 17

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane				
	oral	LD50 > 5000 mg/kg	Rat	Study report (1988)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rat	Study report (1988)	OECD Guideline 402
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran				
	oral	LD50 19800 mg/kg	Rabbit	Publication (1958)	Rabbits were orally gavaged with test ma
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 402
	inhalation (4 h) vapour	LC50 ca. 24,6 mg/l	Rat	AMA Arch. Ind. Hyg. Occ. Med. 10: 61-68	Rats were exposed to 8000 ppm of the tes
13463-67-7	titanium dioxide				
	oral	LD50 > 2000 mg/kg	Rat	Study report (1996)	OECD Guideline 401

Irritation and corrosivity

Causes skin irritation.

Causes serious eye irritation.

Sensitising effects

May cause an allergic skin reaction. (Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane; 2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 12 of 17

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 13 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy) methyl}oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Oncorhynchus mykiss	Study report (1998) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 1,8	72 h	Raphidocelis subcapitata	Study report (1993) OECD Guideline 201
	Acute crustacea toxicity	EL50 mg/l	> 1000	48 h	Daphnia magna	Study report (1998) OECD Guideline 202
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	Study report (1984) OECD Guideline 211
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran					
	Acute fish toxicity	LC50 mg/l	3,6 mg/l	96 h	Oncorhynchus mykiss	Study report (1982) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 100	72 h	Raphidocelis subcapitata	Study report (2007) OECD Guideline 201
	Acute crustacea toxicity	EC50	2,8 mg/l	48 h	Daphnia magna	REACH Registration Dossier OECD Guideline 202
	Crustacea toxicity	NOEC	0,3 mg/l	21 d	Daphnia magna	REACH Registration Dossier OECD Guideline 211
13463-67-7	titanium dioxide					
	Acute fish toxicity	LC50 mg/l	> 100	96 h	Carassius auratus	REACH Registration Dossier OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	> 50	72 h	Raphidocelis subcapitata	REACH Registration Dossier OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	> 100	48 h	Artemia salina	REACH Registration Dossier OECD Guideline 202
	Fish toxicity	NOEC mg/l	>= 80	6 d	Danio rerio	REACH Registration Dossier OECD TG 210
	Algae toxicity	NOEC mg/l	>= 1	32 d	Synedra ulna, Scenedesmus quadricauda, Stigeocloni	Environ. Tox. Chem. 31, 2414-2422 (2012) In this study, the authors report the re
	Crustacea toxicity	NOEC	> 1 mg/l	10 d	Chironomus riparius	REACH Registration Dossier other: OECD Guideline 219

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 14 of 17

Acute bacteria toxicity	(EC50 > 1000 mg/l)	3 h	activated sludge, domestic	REACH Registration Dossier	OECD Guideline 209
-------------------------	--------------------	-----	----------------------------	----------------------------	--------------------

12.2. Persistence and degradability

CAS No	Chemical name	Method	Value	d	Source
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran	OECD 302B	12%	28	
	Not readily biodegradable (according to OECD criteria)				

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	2,7
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran	>= 2,64

BCF

CAS No	Chemical name	BCF	Species	Source
9003-36-5	Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane	150		Other company data (
1675-54-3	2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran	31		Study report (2010)
13463-67-7	titanium dioxide	> 0,47 - < 3,19	Artemia salina	REACH Registration D

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 15 of 17

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number or ID number:</u>	UN 3082
<u>14.2. UN proper shipping name:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1
Transport category:	3
Hazard No:	90
Tunnel restriction code:	-

Inland waterways transport (ADN)

<u>14.1. UN number or ID number:</u>	UN 3082
<u>14.2. UN proper shipping name:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III
Hazard label:	9
Classification code:	M6
Special Provisions:	274 335 375 601
Limited quantity:	5 L
Excepted quantity:	E1

Marine transport (IMDG)

<u>14.1. UN number or ID number:</u>	UN 3082
<u>14.2. UN proper shipping name:</u>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
<u>14.3. Transport hazard class(es):</u>	9
<u>14.4. Packing group:</u>	III
Hazard label:	9
Special Provisions:	274, 335, 969

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 16 of 17

Limited quantity: 5 L
 Excepted quantity: E1
 EmS: F-A, S-F

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 3082
14.2. UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (epoxy resin)
14.3. Transport hazard class(es): 9
14.4. Packing group: III
 Hazard label: 9
 Special Provisions: A97 A158 A197 A215
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y964
 Excepted quantity: E1
 IATA-packing instructions - Passenger: 964
 IATA-max. quantity - Passenger: 450 L
 IATA-packing instructions - Cargo: 964
 IATA-max. quantity - Cargo: 450 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes
 Danger releasing substance: epoxy resin

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
 Entry 3, Entry 75

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:
 Reaction mass of 2,2'-[methylenebis(4,1-phenyleneoxymethylene)]dioxirane and [2-({ 2-[4-(oxiran-2-ylmethoxy)benzyl]phenoxy} methyl)oxirane and [2,2'-[methylenebis(2,1-phenyleneoxymethylene)]dioxirane
 2,2'-[(1-Methylethyliden)bis(4,1-phenyleneoxymethylen)]bisoxiran
 titanium dioxide

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) B (Part A), ARC 855(E) G (Part A)

Revision date: 23.01.2023

Page 17 of 17

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,4,7,8,10,12,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
 (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
 (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
 ICAO: International Civil Aviation Organization
 ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 EC50: Effectice concentration, 50 percent
 DNEL: Derived No Effect Level
 PNEC: Predicted No Effect Concentration
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Skin Irrit. 2; H315	Calculation method
Eye Irrit. 2; H319	Calculation method
Skin Sens. 1; H317	Calculation method
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H372	Causes damage to organs (lung) through prolonged or repeated exposure if inhaled.
H411	Toxic to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)