

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 1 of 17

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ARC 855(E) Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

ARC Polymer Composite to be used with ARC 855(E) (Part A). Repair damage caused by impact, abrasion, erosion or corrosion; rebuild worn areas; fill holes and cracks; provide abrasion resistant surfaces.

Uses advised against

No information available.

1.3. Details of the supplier of the safety data sheet

Company name:	Chesterton International GmbH	
Street:	Am Lenzenfleck 23	
Place:	D-85737 Ismaning GERMANY	
Telephone:	+49 89 99 65 46 - 0	Telefax: +49 89 99 65 46 - 50
e-mail:	eu-sds@chesterton.com	
e-mail (Contact person):	eu-sds@chesterton.com	
Internet:	www.chesterton.com	
Responsible Department:	eu-sds@chesterton.com	

1.4. Emergency telephone number:

+49(0) 551 - 1 92 40 (GIZ-Nord, 24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Acute Tox. 4; H302
Acute Tox. 4; H332
Skin Corr. 1; H314
Eye Dam. 1; H318
Skin Sens. 1; H317

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

3-aminomethyl-3,5,5-trimethylcyclohexylamine
benzyl alcohol
5-Amino-1, 3, 3-trimethylcyclohexanemethanamine reaction products with 2,2'-
[[1-methylethylidene)bis(4,1-phenyloxy)methylene]]bis[ox

Signal word: Danger

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 2 of 17

Pictograms:



Hazard statements

- | | |
|-----------|--|
| H302+H332 | Harmful if swallowed or if inhaled. |
| H314 | Causes severe skin burns and eye damage. |
| H317 | May cause an allergic skin reaction. |

Precautionary statements

- | | |
|----------------|--|
| P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| P264 | Wash hands thoroughly after handling. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P310 | Immediately call a POISON CENTER/doctor. |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |
| P363 | Wash contaminated clothing before reuse. |
| P501 | Dispose of contents/container to an appropriate recycling or disposal facility. |

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 3 of 17

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (Regulation (EC) No 1272/2008)	
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	40 - < 45 %
	220-666-8	
	612-067-00-9	
	01-2119514687-32	
	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Skin Sens. 1A; H302 H314 H318 H317	
100-51-6	benzyl alcohol	40 - < 45 %
	202-859-9	
	603-057-00-5	
	01-2119492630-38	
	Acute Tox. 4, Acute Tox. 4, Eye Irrit. 2; H332 H302 H319	
68609-08-5	5-Amino-1, 3, 3-trimethylcyclohexanemethanamine reaction products with 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxy)methylene]]bis[ox	20 - < 25 %
	614-657-1	
	01-2120106013-80	
	Skin Corr. 1, Eye Dam. 1, Skin Sens. 1, Aquatic Chronic 3; H314 H318 H317 H412	

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
2855-13-2	220-666-8	3-aminomethyl-3,5,5-trimethylcyclohexylamine	40 - < 45 %
		inhalation: LC50 = >5,01 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: ATE 1030 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100	
100-51-6	202-859-9	benzyl alcohol	40 - < 45 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: LC50 = >4,178 mg/l (dusts or mists); dermal: LD50 = > 2000 mg/kg; oral: LD50 = 1580 mg/kg	
68609-08-5	614-657-1	5-Amino-1, 3, 3-trimethylcyclohexanemethanamine reaction products with 2,2'-[[1-methylethylidene]bis(4,1-phenyleneoxy)methylene]]bis[ox	20 - < 25 %
		dermal: LD50 = > 2000 mg/kg; oral: LD50 = 500 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove affected person from the danger area and lay down. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

Remove casualty to fresh air and keep warm and at rest. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, take off immediately all contaminated clothing, and wash immediately with plenty of water and soap. Immediate medical treatment required because corrosive injuries that are not treated are hard to cure.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 4 of 17

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

- Causes severe skin burns and eye damage.
- Allergic reactions
- Gastrointestinal complaints

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- alcohol resistant foam
- Water spray jet
- Carbon dioxide (CO₂)
- Dry extinguishing powder

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated:

- Carbon monoxide
- Carbon dioxide
- Nitrogen oxides (NO_x)

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

- Remove persons to safety.
- Provide adequate ventilation.
- Safe handling: see section 7
- Personal protection equipment: see section 8

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 5 of 17

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Cover drains. Adverse environmental effects

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear personal protection equipment (refer to section 8).

Avoid contact with skin, eyes and clothes.

Avoid breathing dust/fume/gas/mist/vapours/spray.

When using do not eat, drink or smoke.

Never use pressure to empty container. Keep/Store only in original container.

Do not allow to enter into surface water or drains.

Advice on protection against fire and explosion

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on general occupational hygiene

Work in well-ventilated zones or use proper respiratory protection. Only wear fitting, comfortable and clean protective clothing. Avoid contact with skin, eyes and clothes. Wash hands and face before breaks and after work and take a shower if necessary.

Use protective skin cream before handling the product.

Further information on handling

Wash hands before breaks and after work. Used working clothes should not be worn outside the work area.

Street clothing should be stored separately from work clothing.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Keep/Store only in original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Keep away from:

- Frost

- Heat

- Humidity

7.3. Specific end use(s)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 6 of 17

No information available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 7 of 17

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
	Consumer DNEL, acute	oral	systemic	0,3 mg/kg bw/day
	Worker DNEL, long-term	inhalation	local	0,073 mg/m ³
	Worker DNEL, acute	inhalation	local	0,073 mg/m ³
	Consumer DNEL, long-term	oral	systemic	0,3 mg/kg bw/day
100-51-6	benzyl alcohol			
	Worker DNEL, long-term	inhalation	systemic	22 mg/m ³
	Worker DNEL, acute	inhalation	systemic	110 mg/m ³
	Worker DNEL, long-term	dermal	systemic	8 mg/kg bw/day
	Worker DNEL, acute	dermal	systemic	40 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	5,4 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	27 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	4 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	20 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	4 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	20 mg/kg bw/day
68609-08-5	5-Amino-1, 3, 3-trimethylclohexanemethanamine reaction products with 2,2'-[[1-methylethylidene)bis(4,1-phenyloxyethylene)]bis[ox			
	Worker DNEL, long-term	inhalation	systemic	3,29 mg/m ³
	Worker DNEL, acute	inhalation	systemic	9,87 mg/m ³
	Worker DNEL, long-term	dermal	systemic	1,87 mg/kg bw/day
	Consumer DNEL, long-term	inhalation	systemic	0,58 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	1,74 mg/m ³
	Consumer DNEL, long-term	dermal	systemic	0,67 mg/kg bw/day
	Consumer DNEL, long-term	oral	systemic	0,33 mg/kg bw/day
	Consumer DNEL, acute	oral	systemic	0,99 mg/kg bw/day

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 8 of 17

PNEC values

CAS No	Substance	Value
Environmental compartment		
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	
Freshwater		0,06 mg/l
Freshwater (intermittent releases)		0,23 mg/l
Marine water		0,006 mg/l
Freshwater sediment		5,784 mg/kg
Marine sediment		0,578 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,18 mg/l
Soil		1,121 mg/kg
100-51-6	benzyl alcohol	
Freshwater		1 mg/l
Freshwater (intermittent releases)		2,3 mg/l
Marine water		0,1 mg/l
Freshwater sediment		5,27 mg/kg
Marine sediment		0,527 mg/kg
Micro-organisms in sewage treatment plants (STP)		39 mg/l
Soil		0,456 mg/kg
68609-08-5	5-Amino-1, 3, 3-trimethylclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleoxymethylene)]bis[ox	
Freshwater		0,002 mg/l
Freshwater (intermittent releases)		0,016 mg/l
Marine water		0 mg/l
Freshwater sediment		10,5 mg/kg
Marine sediment		1,05 mg/kg
Micro-organisms in sewage treatment plants (STP)		3,1 mg/l
Soil		2,1 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment

Eye/face protection

Suitable eye protection:

Eye glasses with side protection

goggles

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 9 of 17

Hand protection

Tested protective gloves must be worn: EN ISO 374
 NBR (Nitrile rubber), Butyl caoutchouc (butyl rubber)
 Thickness of the glove material $\geq 0,4$ mm
 Breakthrough times and swelling properties of the material must be taken into consideration.
 For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.
 Wearing time with occasional contact (splashes): max. 480 min. (NBR (Nitrile rubber))
 Wearing time with permanent contact 240 - 480 min (NBR (Nitrile rubber))
 Observe the wear time limits as specified by the manufacturer.

Skin protection

Protective clothing

Respiratory protection

Usually no personal respirative protection necessary.
 If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn.
 Combination filtering device A-P3
 Self-contained respirator (breathing apparatus)

Thermal hazards

No data available

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	clear - colourless
Odour:	Ammonia (NH ₃)

Melting point/freezing point:	No data available
Boiling point or initial boiling point and boiling range:	> 200 °C
Flammability	
Solid/liquid:	No data available
Gas:	No data available
Lower explosion limits:	not applicable
Upper explosion limits:	not applicable
Flash point:	> 100 °C
Auto-ignition temperature:	No data available
Decomposition temperature:	No data available
pH-Value:	10 - 11
Water solubility:	Immiscible

Test method

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 10 of 17

Solubility in other solvents

No information available.

Partition coefficient n-octanol/water:

No data available

Vapour pressure:

No data available

Density (at 23 °C):

1 g/cm³

Relative vapour density:

>1 (Air=1)

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

No information available.

Self-ignition temperature

Solid:

No data available

Gas:

No data available

Oxidizing properties

No information available.

Other safety characteristics

Evaporation rate:

<1 (Ether=1)

Viscosity / dynamic:
(at 25 °C)

260 mPa·s

Further Information

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is stable under storage at normal ambient temperatures.

10.2. Chemical stability

Does not decompose when used for intended uses.

10.3. Possibility of hazardous reactions

No information available.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

- Strong acid,
- Oxidising agent

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 11 of 17

Acute toxicity

Harmful if swallowed.

Harmful if inhaled.

ATEmix calculated

ATE (oral) 1558,8 mg/kg; ATE (inhalation vapour) 27,50 mg/l; ATE (inhalation dust/mist) 3,750 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine				
	oral	ATE 1030 mg/kg			
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2010)	OECD Guideline 402
	inhalation (4 h) dust/mist	LC50 >5,01 mg/l	Rat		
100-51-6	benzyl alcohol				
	oral	LD50 1580 mg/kg	Mouse	Cosmet. Toxicol. 11, 1011-1013 (1973) (1)	OECD Guideline 401
	dermal	LD50 > 2000 mg/kg	Rabbit	Raw Material Data Handbook, Vol.1:(Orga	EPA OTS 798.1100
	inhalation vapour	ATE 11 mg/l			
	inhalation (4 h) dust/mist	LC50 >4,178 mg/l	Rat	ECHA	OECD 403
68609-08-5	5-Amino-1, 3, 3-trimethylclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleoxymethylene)]bis[ox				
	oral	LD50 500 mg/kg	Rat	Study report (2007)	OECD Guideline 423
	dermal	LD50 > 2000 mg/kg	Rat	Study report (2007)	OECD Guideline 402

Irritation and corrosivity

Causes severe skin burns and eye damage.

Causes serious eye damage.

Sensitising effects

May cause an allergic skin reaction. (3-aminomethyl-3,5,5-trimethylcyclohexylamine; 5-Amino-1, 3, 3-trimethylclohexanemethanamine reaction products with 2,2'-[(1-methylethylidene)bis(4,1-phenyleoxymethylene)]bis[ox)

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 12 of 17

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Endocrine disrupting properties

No data available

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 13 of 17

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine					
	Acute fish toxicity	LC50 110 mg/l	96 h	Leuciscus idus	REACH Registration Dossier	EU Method C.1
	Acute algae toxicity	ErC50 37 mg/l	72 h	Desmodesmus subspicatus	REACH Registration Dossier	EU Method C.3
	Acute crustacea toxicity	EC50 23 mg/l	48 h	Daphnia magna	REACH Registration Dossier	OECD Guideline 202
	Crustacea toxicity	NOEC 3 mg/l	21 d	Daphnia magna	REACH Registration Dossier	other: OECD 202, part 2
100-51-6	benzyl alcohol					
	Acute fish toxicity	LC50 > 100 mg/l	96 h	Oryzias latipes	Review article or handbook (2009)	OECD Guideline 203
	Acute algae toxicity	ErC50 770 mg/l	72 h	Raphidocelis subcapitata	Review article or handbook (2009)	OECD Guideline 201
	Acute crustacea toxicity	EC50 230 mg/l	48 h	Daphnia magna	Review article or handbook (2009)	OECD Guideline 202
	Fish toxicity	NOEC 48,897 mg/l	30 d	Fish species	http://epa.gov/oppt/exposure/pubs/episui	other: QSAR
	Algae toxicity	NOEC 51 mg/l	3 d			
	Crustacea toxicity	NOEC 51 mg/l	21 d	Daphnia magna	Review article or handbook (2009)	OECD Guideline 211
	Acute bacteria toxicity	(EC50 1385 mg/l)	3 h	activated sludge, domestic	Study report (1989)	OECD Guideline 209
68609-08-5	5-Amino-1, 3, 3-trimethylcyclohexanemethanamine reaction products with 2,2'-[[1-methylethylidene)bis(4,1-phenyloxy)methylene)]bis[ox					
	Acute fish toxicity	LC50 1,62 mg/l	96 h	Danio rerio	REACH Registration Dossier	EU Method C.1
	Acute algae toxicity	ErC50 3,13 mg/l	72 h	Raphidocelis subcapitata	REACH Registration Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 1,75 mg/l	48 h	Daphnia magna	REACH Registration Dossier	EU Method C.2
	Acute bacteria toxicity	(EC50 72,63 mg/l)	3 h	Activated sludge	REACH Registration Dossier	EU Method C.11

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 14 of 17

12.2. Persistence and degradability

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine			
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	8 %	28	
	Not readily biodegradable (according to OECD criteria)			
100-51-6	benzyl alcohol			
	OECD 301A/ ISO 7827/ EEC 92/69/V, C.4-A	95 - 97%	21	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	0,99
100-51-6	benzyl alcohol	1
68609-08-5	5-Amino-1, 3, 3-trimethylcyclohexanemethanamine reaction products with 2,2'-[[1-methylethylidene]bis(4,1-phenyloxyethylene)]bis[ox	2,36

BCF

CAS No	Chemical name	BCF	Species	Source
2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine	2,63		REACH Registration D
100-51-6	benzyl alcohol	1,371	QSAR model	http://epa.gov/oppt/

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 15 of 17

Contaminated packaging

Non-contaminated packages may be recycled. Dispose of waste according to applicable legislation.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Cycloaliphatic amine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	80
Tunnel restriction code:	E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Cycloaliphatic amine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Classification code:	C7
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2

Marine transport (IMDG)

14.1. UN number or ID number:	UN 2735
14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Cycloaliphatic amine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	274
Limited quantity:	1 L
Excepted quantity:	E2
EmS:	F-A, S-B
Segregation group:	18 - alkalis

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	UN 2735
--------------------------------------	---------

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 16 of 17

14.2. UN proper shipping name:	AMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine, Cycloaliphatic amine)
14.3. Transport hazard class(es):	8
14.4. Packing group:	II
Hazard label:	8
Special Provisions:	A3 A803
Limited quantity Passenger:	0.5 L
Passenger LQ:	Y840
Excepted quantity:	E2
IATA-packing instructions - Passenger:	851
IATA-max. quantity - Passenger:	1 L
IATA-packing instructions - Cargo:	855
IATA-max. quantity - Cargo:	30 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

No information available.

14.7. Maritime transport in bulk according to IMO instruments

No information available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):
Entry 3

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

For the following substances of this mixture a chemical safety assessment has been carried out:

3-aminomethyl-3,5,5-trimethylcyclohexylamine

benzyl alcohol

5-Amino-1, 3, 3-trimethylcyclohexanemethanamine reaction products with 2,2'-

[(1-methylethylidene)bis(4,1-phenyloxy)methylene]]bis[ox

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 2,8,9,10,12,14,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

Safety Data Sheet

according to Regulation (EC) No 1907/2006

ARC 855(E) Part B

Revision date: 24.01.2023

Page 17 of 17

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer
 (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CLP: Regulation on Classification, Labelling and Packaging of Substances and Mixtures,

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

EC50: Effective concentration, 50 percent

DNEL: Derived No Effect Level

PNEC: Predicted No Effect Concentration

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Acute Tox. 4; H302	Calculation method
Acute Tox. 4; H332	Calculation method
Skin Corr. 1; H314	Calculation method
Eye Dam. 1; H318	Calculation method
Skin Sens. 1; H317	Calculation method

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H302+H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H412	Harmful to aquatic life with long lasting effects.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)