

**SAFETY DATA SHEET**

in accordance with REACH (1907/2006/EC, as amended by 2015/830/EU) 29 CFR 1910.1200 and WHMIS 2015

**Revision date:** 30 April 2019

**Initial date of issue:** 6 July 2007

**SDS No.** 234A-21

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

ARC 855B (Part A), ARC 855G (Part A)

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

ARC Polymer Composite. Repair damage caused by impact, abrasion, erosion or corrosion; rebuild worn areas; fill holes and cracks; provide abrasion resistant surfaces.

**1.3. Details of the supplier of the safety data sheet**

**Company:**

A.W. CHESTERTON COMPANY  
860 Salem Street  
Groveland, MA 01834-1507, USA  
Tel. +1 978-469-6446 Fax: +1 978-469-6785  
(Mon. - Fri. 8:30 - 5:00 PM EST)  
SDS requests: www.chesterton.com  
E-mail (SDS questions): ProductMSDSs@chesterton.com  
E-mail: customer.service@chesterton.com

**Supplier:**

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,  
Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055  
EU: Chesterton International GmbH, Am Lenzenfleck 23,  
D85737 Ismaning, Germany – Tel. +49-89-996-5460

**1.4. Emergency telephone number**

24 hours per day, 7 days per week  
Call Infotrac: 1-800-535-5053  
Outside N. America: +1 352-323-3500 (collect)  
NSW Poisons Information Centre (Australia): 13 11 26

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS**

Skin irritation, Category 2, H315  
Eye irritation, Category 2, H319  
Skin sensitization, Category 1, H317  
Hazardous to the aquatic environment, Chronic, Category 2, H411

**2.1.2. Australian statement of hazardous nature**

Hazardous according to criteria of Safe Work Australia.

**2.1.3. Additional information**

For full text of H-statements: see SECTIONS 2.2 and 16.

**2.2. Label elements**

**Labelling according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / GHS**

**Hazard pictograms:**



**Signal word:**

Warning

<b>Hazard statements:</b>	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H317	May cause an allergic skin reaction.
	H411	Toxic to aquatic life with long lasting effects.
<b>Precautionary statements:</b>	P264	Wash skin thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves and eye/face protection.
	P302/352	IF ON SKIN: Wash with plenty of soap and water.
	P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P333/313	If skin irritation or rash occurs: Get medical advice/attention.
	P337/313	If eye irritation persists: Get medical advice/attention.
	P362/364	Take off contaminated clothing and wash it before reuse.
	P391	Collect spillage.
	P501	Dispose of contents/container to an approved waste disposal plant.

**Supplemental information:** None

### 2.3. Other hazards

The safety and health hazards are detailed separately for Part A and Part B. The final cured material is considered nonhazardous. Upon machining, refer to the precautions in the safety data sheets for Part A and Part B.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2. Mixtures

Hazardous Ingredients <sup>1</sup>	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification
Epoxy resin (number average molecular weight <= 700)	10-30	9003-36-5* 500-006-8	NA	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Epoxy resin (number average molecular weight <= 700)	10-30	25068-38-6 500-033-5	NA	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Other ingredients:				
Silicon carbide	15-40	409-21-2 206-991-8	NA	Not classified**
Graphite	1-5	7782-42-5 231-955-3	NA	Not classified**
Silica (Quartz)	1-5	14808-60-7 238-878-4	NA	Not classified**
Titanium dioxide	0-4	13463-67-7 236-675-5	NA	Not classified**

\*Alternative CAS No: 28064-14-4.

\*\*Substance with a workplace exposure limit.

For full text of H-statements: see SECTION 16.

<sup>1</sup> Classified according to: • 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F)  
• 1272/2008/EC, GHS, REACH  
• WHMIS 2015  
• Safe Work Australia

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

**Inhalation:** Not applicable

**Skin contact:** Remove contaminated clothing. Wash skin with soap and water. Consult physician if irritation develops.

**Eye contact:** Flush eyes for at least 15 minutes with large amounts of water. Consult physician if irritation develops.

**Ingestion:** Do not induce vomiting. Contact physician immediately.

**Protection of first-aiders:** No action shall be taken involving any personal risk or without suitable training. Avoid contact with the product while providing aid to the victim. See section 8.2.2 for recommendations on personal protective equipment.

**4.2. Most important symptoms and effects, both acute and delayed**

Moderate eye and skin irritant. May cause skin sensitization as evidenced by rashes or hives.

**4.3. Indication of any immediate medical attention and special treatment needed**

Treat symptoms.

**SECTION 5: FIREFIGHTING MEASURES****5.1. Extinguishing media**

**Suitable extinguishing media:** Carbon dioxide, dry chemical, foam or water fog

**Unsuitable extinguishing media:** None known

**5.2. Special hazards arising from the substance or mixture**

Hazardous combustion products may include: phenolics, carbon monoxide, carbon dioxide, halogenated compounds,

**5.3. Advice for firefighters**

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus.

**Flammability Classification:** –

**HAZCHEM Emergency Action Code:** 2 Z

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1. Personal precautions, protective equipment and emergency procedures**

Avoid skin contact. Utilize exposure controls and personal protection as specified in Section 8.

**6.2. Environmental Precautions**

Keep out of sewers, streams and waterways.

**6.3. Methods and material for containment and cleaning up**

Contain spill to a small area. Pick up with absorbent material (sand, sawdust, clay, etc.) and place in a suitable container for disposal.

**6.4. Reference to other sections**

Refer to section 13 for disposal advice.

**SECTION 7: HANDLING AND STORAGE****7.1. Precautions for safe handling**

Remove contaminated clothing immediately. Wash clothing before reuse. Contaminated leather including shoes cannot be decontaminated and should be discarded. Contaminated work clothing must not be allowed out of the workplace. Utilize exposure controls and personal protection as specified in Section 8. Wash thoroughly after handling. Avoid creating and breathing dust during removal, drilling, grinding, sawing or sanding.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, dry area.

**7.3. Specific end use(s)**

No special precautions.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL <sup>1</sup>		ACGIH TLV <sup>2</sup>		UK WEL <sup>3</sup>		AUSTRALIA ES <sup>4</sup>	
	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Epoxy resin (number average molecular weight <= 700)	–	–	–	–	–	–	–	–
Silicon carbide	(total)	15	(total)	10	(total)	10	(inhal.)	10
	(resp.)	5	(resp.)	3	(resp.)	4		
Graphite	15 mppcf	(resp.)	(resp.)	2	(inhal.)	10	(resp.)	3
					(resp.)	4		
Silica (Quartz)	(total)	30/(%silic	(resp.)	0.025	–	0.1	(resp.)	0.1
	(resp.)	a+2)						
		0.05						
Titanium dioxide	–	15	–	10	(total)	10	(inhal.)	10
					(resp.)	4		

<sup>1</sup> United States Occupational Health & Safety Administration permissible exposure limits

<sup>2</sup> American Conference of Governmental Industrial Hygienists threshold limit values

<sup>3</sup> EH40 Workplace exposure limits, Health & Safety Executive

<sup>4</sup> Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

**Biological limit values**

Not available

**Derived No Effect Level (DNEL) according to Regulation (EC) No 1907/2006:****Workers**

Substance	Route of exposure	Potential health effects	DNEL
Epoxy resin (CAS no. 9003-36-5)	Inhalation	Acute effects, local / Acute effects, systemic	no data available
		Chronic effects, local	no data available
		Chronic effects, systemic	29.39 mg/m <sup>3</sup>
	Dermal	Acute effects, local	0.0083 mg/cm <sup>2</sup>
		Acute effects, systemic	no data available
		Chronic effects, systemic	104.15 mg/kg bw/day
Graphite	Inhalation	Chronic effects, local	1.2 mg/m <sup>3</sup>
Titanium dioxide	Inhalation	Chronic effects	10 mg/m <sup>3</sup>

**Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006:**

Substance	Environmental protection target	PNEC
Epoxy resin (CAS no. 9003-36-5)	Fresh water	0.003 mg/l
	Marine water	0.0003 mg/l
	Water, intermittent release	0.0254 mg/l
	Freshwater sediments	0.294 mg/kg
	Marine sediments	0.0294 mg/kg
	Microorganisms in sewage treatment	10 mg/l
Titanium dioxide	Soil (agricultural)	0.237 mg/kg
	Fresh water	0.184 mg/l
	Marine water	0.0184 mg/l
	Water	0.193 mg/l
	Freshwater sediments	1000 mg/kg
	Marine sediments	100 mg/kg
	Microorganisms in sewage treatment	100 mg/l
	Soil (agricultural)	100 mg/kg

**8.2. Exposure controls****8.2.1. Engineering measures**

No special requirements. If exposure limits are exceeded, provide adequate ventilation. If it is necessary to alter the final cured product such that dust may be generated, use adequate dust extraction or damp down.

**8.2.2. Individual protection measures**

**Respiratory protection:** Not normally needed. If exposure limits are exceeded, use a half or full-face respirator with combined dust/organic vapour filter (e.g., EN filter type A-P2).

**Protective gloves:** Chemical resistant gloves (e.g., nitrile rubber, butyl rubber, neoprene, PVC)

**Eye and face protection:** Safety goggles.

**Other:** Impervious clothing as necessary to prevent skin contact.

**8.2.3. Environmental exposure controls**

Refer to sections 6 and 12.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	viscous liquid	<b>Odour</b>	sweet
<b>Colour</b>	black or gray	<b>Odour threshold</b>	not determined
<b>Initial boiling point</b>	not applicable	<b>Vapour pressure @ 20°C</b>	not determined
<b>Melting point</b>	not applicable	<b>% Aromatics by weight</b>	0%
<b>% Volatile (by volume)</b>	< 1%	<b>pH</b>	not applicable
<b>Flash point</b>	249°C (480°F)	<b>Relative density</b>	1.9 – 2.0 kg/l
<b>Method</b>	Closed Cup	<b>Weight per volume</b>	15.8 – 16.6 lbs/gal.
<b>Viscosity</b>	700k – 3.3MM cps @ 25°C	<b>Coefficient (water/oil)</b>	< 1
<b>Autoignition temperature</b>	not applicable	<b>Vapour density (air=1)</b>	> 1
<b>Decomposition temperature</b>	not determined	<b>Rate of evaporation (ether=1)</b>	< 1
<b>Upper/lower flammability or explosive limits</b>	not determined	<b>Solubility in water</b>	very slight
<b>Flammability (solid, gas)</b>	not applicable	<b>Oxidising properties</b>	not determined
<b>Explosive properties</b>	not determined		

**9.2. Other information**

None

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

Refer to sections 10.3 and 10.5.

**10.2. Chemical stability**

Stable

**10.3. Possibility of hazardous reactions**

No dangerous reactions known under conditions of normal use.

**10.4. Conditions to avoid**

Extreme heat above 149°C (300°F).

**10.5. Incompatible materials**

Strong mineral acids and bases, strong organic bases and strong oxidizers like liquid Chlorine and concentrated Oxygen.

**10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects**

**Primary route of exposure under normal use:** Skin and eye contact. Personnel with pre-existing skin or lung allergies may be aggravated by exposure.

**Acute toxicity -**

**Oral:** Based on available data on components, the classification criteria are not met.

Substance	Test	Result
Epoxy resin	LD50, rat	> 5000 mg/kg
Graphite	LD50, rat	> 2000 mg/kg
Silicon carbide	NOAEL, rat	2000 mg/kg
Titanium dioxide	LD50, rat	> 10000 mg/kg

**Dermal:**

Substance	Test	Result
Epoxy resin	LD50, rabbit	> 2000 mg/kg
Silicon carbide	NOAEL, rat	2000 mg/kg
Titanium dioxide	LD50, rabbit	> 10000 mg/kg

**Inhalation:**

Substance	Test	Result
Epoxy resin (CAS no. 25068-38-6)	LC0, rat, 5-8 h	No mortality at vapor saturation level
Graphite	LC50, rat, 4 h	> 2 mg/l
Titanium dioxide	LC50, rat, 4 h	> 6.82 mg/l

**Skin corrosion/irritation:** Irritating to skin.

Substance	Test	Result
Epoxy resin	Skin irritation, rabbit	Mild irritation
Graphite	Skin irritation, rabbit	Not irritating
Titanium dioxide	Skin irritation, rabbit	Not irritating

**Serious eye damage/irritation:**

Irritating to eyes.

Substance	Test	Result
Epoxy resin (CAS no. 25068-38-6)	Eye irritation, rabbit	Mild irritation / Moderate irritation
Titanium dioxide	Eye irritation, rabbit	Not irritating

**Respiratory or skin sensitisation:**

May cause skin sensitization as evidenced by rashes or hives.

Substance	Test	Result
Epoxy resin	Skin sensitization, guinea pig	Sensitizing
Graphite	Skin sensitization, mouse	Not sensitizing
Titanium dioxide	Skin sensitization, guinea pig	Not sensitizing

**Germ cell mutagenicity:** Epoxy resin, Silicon carbide, Titanium dioxide: based on available data, the classification criteria are not met.

**Carcinogenicity:** The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) have classified inhaled silica as a human carcinogen. IARC has designated inhaled titanium dioxide as possibly carcinogenic to humans (group 2B). The silica and titanium dioxide in this product do not separate from the mixture or in of themselves become airborne, therefore, do not present a hazard in normal use. Epoxy resin: based on available data, the classification criteria are not met.

**Reproductive toxicity:** Epoxy resin, Graphite, Silicon carbide, Titanium dioxide: based on available data, the classification criteria are not met.

**STOT – single exposure:** Not expected to cause toxicity.

**STOT – repeated exposure:** Repeated inhalation of respirable free silica may cause scarring of the lungs with cough and shortness of breath. Silicosis, a delayed lung injury that is a disabling, progressive and sometimes fatal pulmonary fibrosis, may result. Prolonged, excessive inhalation of Graphite dust has caused emphysema and pneumoconiosis. The silica and graphite in this product do not separate from the mixture or in of themselves become airborne, therefore, do not present a hazard in normal use. Epoxy resin: not expected to cause toxicity.

Substance	Test	Result
Epoxy resin (CAS no. 25068-38-6)	Sub-chronic NOAEL, oral, 90 days, rat, male / female (OECD 408)	50 mg/kg bw/day
Epoxy resin (CAS no. 25068-38-6)	Sub-chronic NOAEL, dermal, 90 days, rat, male / female (OECD 411)	10 mg/kg bw/day
Epoxy resin (CAS no. 25068-38-6)	Sub-chronic NOAEL, dermal, 90 days, mouse, male (OECD 411)	100 mg/kg bw/day
Epoxy resin (CAS no. 9003-36-5)	Sub-chronic NOAEL, oral, 90 days, rat, male / female (OECD 408)	250 mg/kg bw/day

**Aspiration hazard:** Based on available data, the classification criteria are not met.

**Other information:** None known

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

### 12.1. Toxicity

Epoxy resin (number average molecular weight  $\leq$  700) is toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment (LC50/EC50 between 1 and 10 mg/l in the most sensitive species). Epoxy resin: chronic NOEC, 21 days, *Daphnia magna* (OECD 211) = 0.3 mg/l.

### 12.2. Persistence and degradability

Unreacted components (Parts A and B), improperly released to the environment, can cause ground and water pollution. Epoxy resin: not readily biodegradable (biodegradation, OECD 301F, 28 days: 5%).

### 12.3. Bioaccumulative potential

Epoxy resin: Octanol/water partition coefficient (log Kow) = 2.64 – 3.78, low to moderate potential for bioaccumulation.

### 12.4. Mobility in soil

Viscous liquid. Solubility in water: very slight. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Epoxy resin: if product enters soil, it will be mobile and may contaminate groundwater (log Koc  $\leq$  3.65).

### 12.5. Results of PBT and vPvB assessment

Not available

### 12.6. Other adverse effects

None known

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

Combine resin and curative. The final cured material is considered nonhazardous. Unreacted components are a special waste. Landfill sealed containers with stabilized and solidified liquids in a properly licensed facility. May be incinerated at an appropriate facility. Check local, state and national/federal regulations and comply with the most stringent requirement. The unhardened product is classified as a hazardous waste according to 2008/98/EC.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. UN number

**ADG/ADR/RID/ADN/IMDG/ICAO:** UN3082

**TDG:** UN3082

**US DOT:** UN3082

### 14.2. UN proper shipping name

**ADG/ADR/RID/ADN/IMDG/ICAO:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

**TDG:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)

<b>US DOT:</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (EPOXY RESIN)
<b>14.3. Transport hazard class(es)</b>	
<b>ADG/ADR/RID/ADN/IMDG/ICAO:</b>	9
<b>TDG:</b>	9
<b>US DOT:</b>	9
<b>14.4. Packing group</b>	
<b>ADG/ADR/RID/ADN/IMDG/ICAO:</b>	III
<b>TDG:</b>	III
<b>US DOT:</b>	III
<b>14.5. Environmental hazards</b>	
MARINE POLLUTANT	
<b>14.6. Special precautions for user</b>	
NO SPECIAL PRECAUTIONS FOR USER	
<b>14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	
NOT APPLICABLE	
<b>14.8. Other information</b>	
<b>US DOT:</b> ERG NO.171, May be shipped as NON-RESTRICTED in non-bulk packagings (119 gallons or less) by motor vehicle, rail car or aircraft. (49 CFR 171.4(c))	
<b>IMDG:</b> EmS. F-A, S-F May be shipped as NON-RESTRICTED in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less. (IMDG CODE Amendment 37-14, 2.10.2.7)	
<b>ICAO/IATA:</b> May be shipped as NON-RESTRICTED in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less.(IATA Dangerous Goods Regulation 56 <sup>th</sup> edition, 4.4 Special Provisions A197)	
<b>ADR:</b> Classification code M6 Tunnel restriction code (E) May be shipped as NON-RESTRICTED in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less. (ADR 2015 Volume 1, Chapter 3.3 Special Provisions 375)	
<b>ADG HAZCHEM CODE:</b> ●3Z <b>HIN:</b> 90	

**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

**Authorisations under Title VII:** Not applicable

**Restrictions under Title VIII:** None

**Other EU regulations:** Directive 94/33/EC on the protection of young people at work.

**15.1.2. National regulations****US EPA SARA TITLE III****312 Hazards:**

Skin irritation  
Eye irritation  
Skin sensitization

**313 Chemicals:**

None

**Other national regulations:** National implementation of the EC Directive referred to in section 15.1.1.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.



**SECTION 16: OTHER INFORMATION**

**Abbreviations and acronyms:** ADG: Australian Dangerous Goods Code  
 ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ATE: Acute Toxicity Estimate  
 BCF: Bioconcentration Factor  
 cATpE: Converted Acute Toxicity point Estimate  
 CLP: Classification Labelling Packaging Regulation (1272/2008/EC)  
 ES: Exposure Standard  
 GHS: Globally Harmonized System  
 ICAO: International Civil Aviation Organization  
 IMDG: International Maritime Dangerous Goods  
 LC50: Lethal Concentration to 50 % of a test population  
 LD50: Lethal Dose to 50% of a test population  
 LOEL: Lowest Observed Effect Level  
 N/A: Not Applicable  
 NA: Not Available  
 NOEC: No Observed Effect Concentration  
 NOEL: No Observed Effect Level  
 OECD: Organization for Economic Co-operation and Development  
 PBT: Persistent, Bioaccumulative and Toxic substance  
 (Q)SAR: Quantitative Structure-Activity Relationship  
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)  
 REL: Recommended Exposure Limit  
 RID: Regulations concerning the International Carriage of Dangerous Goods by Rail  
 SDS: Safety Data Sheet  
 STEL: Short Term Exposure Limit  
 STOT RE: Specific Target Organ Toxicity, Repeated Exposure  
 STOT SE: Specific Target Organ Toxicity, Single Exposure  
 TDG: Transportation of Dangerous Goods (Canada)  
 TWA: Time Weighted Average  
 US DOT: United States Department of Transportation  
 vPvB: very Persistent and very Bioaccumulative substance  
 WEL: Workplace Exposure Limit  
 WHMIS: Workplace Hazardous Materials Information System  
 Other abbreviations and acronyms can be looked up at [www.wikipedia.org](http://www.wikipedia.org).

**Key literature references and sources for data:** Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)  
 Chemical Classification and Information Database (CCID)  
 European Chemicals Agency (ECHA) - Information on Chemicals  
 Hazardous Chemical Information System (HCIS)  
 National Institute of Technology and Evaluation (NITE)  
 Swedish Chemicals Agency (KEMI)  
 U.S. National Library of Medicine Toxicology Data Network (TOXNET)

**Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP] / GHS:**

Classification	Classification procedure
Skin Irrit. 2, H315	Calculation method
Eye Irrit. 2, H319	Calculation method
Skin Sens. 1, H317	Calculation method
Aquatic Chronic 2, H411	Calculation method

**Relevant H-statements:** H315: Causes skin irritation.  
 H317: May cause an allergic skin reaction.  
 H319: Causes serious eye irritation.  
 H411: Toxic to aquatic life with long lasting effects.

**Hazard pictogram names:** Exclamation mark, environment.

**Further information:** None

**Date of last revision:** 30 April 2019

**Changes to the SDS in this revision:** Sections 2.1, 3, 5.2, 8.1, 9.1, 10.6, 11, 12.1, 12.3, 13, 15.1.2, 16.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.