

SAFETY DATA SHEET

in accordance with 2020/878/EU (REACH, Annex II) 29 CFR 1910.1200, WHMIS 2015 and Safe Work Australia

Revision date: 11 August 2023

Date of previous issue: 27 April 2021

SDS No. 293B-13

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

ARC MX1 (Part B)

Unique Formula Identifier (UFI): Not available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: To be used with parts A and C for abrasion resistant surfaces.

Uses advised against: No information available

Reason why uses advised against: Not applicable

1.3. Details of the supplier of the safety data sheet

Company:

A.W. CHESTERTON COMPANY

860 Salem Street

Groveland, MA 01834-1507, USA

Tel. +1 978-469-6446 Fax: +1 978-469-6785

(Mon. - Fri. 8:30 - 5:00 PM EST)

SDS requests: www.chesterton.com

E-mail (SDS questions): ProductSDSs@chesterton.com

E-mail: customer.service@chesterton.com

Supplier:

Canada: A.W. Chesterton Company Ltd., 889 Fraser Drive,

Unit 105, Burlington, Ontario L7L 4X8 – Tel. 905-335-5055

EU: Chesterton International GmbH, Am Lenzenfleck 23,

D85737 Ismaning, Germany – Tel. +49-89-996-5460

1.4. Emergency telephone number

24 hours per day, 7 days per week

Call Infotrac: 1-800-535-5053

Outside N. America: +1 352-323-3500 (collect)

NSW Poisons Information Centre (Australia): 13 11 26

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

2.1.1. Classification according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / Safe Work Australia / GHS

Acute toxicity, Category 4, H302

Skin corrosion, Category 1B, H31

Serious eye damage, Category 1, H318

Skin sensitization, Category 1, H317

Specific target organ toxicity – single exposure, Category 3, H335

2.1.2. Additional information

For full text of H-statements: see SECTIONS 2.2 and 16.

2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP] / 29 CFR 1910.1200 / WHMIS 2015 / Safe Work Australia / GHS

Hazard pictograms:



Signal word:

Danger

Hazard statements:	H302	Harmful if swallowed.
	H314	Causes severe skin burns and eye damage.
	H317	May cause an allergic skin reaction.
	H335	May cause respiratory irritation.
Precautionary statements:	P261	Avoid breathing vapours.
	P264	Wash hands thoroughly after handling.
	P270	Do not eat, drink or smoke when using this product.
	P271	Use only outdoors or in a well-ventilated area.
	P280	Wear protective gloves/clothing and eye/face protection.
	P303/361/353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
	P304/340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305/351/338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P301/330/331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
	P310	Immediately call a POISON CENTER or doctor.
	P333/313	If skin irritation or rash occurs: Get medical advice/attention.
	P363	Wash contaminated clothing before reuse.
	P403/233	Store in a well-ventilated place. Keep container tightly closed.
	P405	Store locked up.
	P501	Dispose of contents/container to an approved waste disposal plant.
Supplemental information:	None	

2.3. Other hazards

The safety and health hazards are detailed separately for Part A, Part B and Part C. The final cured material is considered nonhazardous. Upon machining, refer to the precautions in the safety data sheets for Part A, Part B and Part C.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures**

Hazardous Ingredients ¹	% Wt.	CAS No./ EC No.	REACH Reg. No.	CLP/GHS Classification	SCL, M-factor, ATE
1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with bisphenol A diglycidyl ether homopolymer	40-60	68411-71-2 270-141-2	NA	Acute Tox. 4, H302	ATE (oral): 500 mg/kg
Diethylenetriamine*	15-25	111-40-0 203-865-4	NA	Acute Tox. 2, H330 Acute Tox. 4, H312/H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 STOT SE 3, H335	ATE (oral): 1,553 mg/kg ATE (dermal): 1,045 mg/kg ATE (inhalation, mist): > 0.07 mg/l
Other ingredients: Titanium dioxide**	5-10	13463-67-7 236-675-5	NA	Not classified***	ATE (oral): 10,000 mg/kg ATE (dermal): > 10,000 mg/kg ATE (inhalation, dust): > 6.82 mg/l
Iron oxide	1-5	1309-37-1 215-168-2	NA	Not classified***	ATE (oral): > 5,000 mg/kg

For full text of H-statements: see SECTION 16.

* This component is toxic by inhalation if sprayed or if aerosol/mist is created. The mixture is neither present in aerosol form nor may aerosols occur.

** Contains less than 1 % of particles with aerodynamic diameter ≤ 10 µm.

*** Substance with a workplace exposure limit.

¹ Classified according to: • 29 CFR 1910.1200, 1915, 1916, 1917, Mass. Right-to-Know Law (ch. 40, M.G.L..O. 111F)
• 1272/2008/EC, GHS, REACH
• WHMIS 2015
• Safe Work Australia

SECTION 4: FIRST AID MEASURES**4.1. Description of first aid measures**

- Inhalation:** Remove to fresh air. If not breathing, administer artificial respiration. Contact physician.
- Skin contact:** Flood area with water while removing contaminated clothing. Contact physician.
- Eye contact:** Flush eyes for at least 30 minutes with large amounts of water. Contact physician.
- Ingestion:** Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. If person is conscious, rinse mouth with water and give small quantities of water to drink. Prevent aspiration of vomit. Turn victim's head to the side. Contact physician immediately.
- Protection of first-aiders:** No action shall be taken involving any personal risk or without suitable training. Avoid contact with the product while providing aid to the victim. Avoid breathing vapours. See section 8.2.2 for recommendations on personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Corrosive to eyes, skin and mucous membranes, which can result in strong irritation, burning and tissue damage. Vapors can be severely irritating to the eyes and respiratory tract. May cause skin sensitization as evidenced by rashes or hives.

4.3. Indication of any immediate medical attention and special treatment needed

Similar to ammonia, this product is highly injurious to all tissues. No specific treatment. Treat symptoms.

SECTION 5: FIREFIGHTING MEASURES**5.1. Extinguishing media**

- Suitable extinguishing media:** Carbon dioxide, dry chemical, dry sand, limestone powder, alcohol-resistant foam
- Unsuitable extinguishing media:** No data available

5.2. Special hazards arising from the substance or mixture

- Hazardous combustion products:** Incomplete combustion may form carbon monoxide. May generate: ammonia gas, toxic nitrogen oxide gases.

Other hazards: None

5.3. Advice for firefighters

Cool exposed containers with water. Recommend Firefighters wear self-contained breathing apparatus and complete fire service protective equipment.

Australian HAZCHEM Emergency Action Code: 3 X

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Provide adequate ventilation. Utilize exposure controls and personal protection as specified in Section 8.

6.2. Environmental Precautions

Keep out of sewers, streams and waterways.

6.3. Methods and material for containment and cleaning up

Contain spill to a small area. Scoop up and transfer to a suitable container for disposal.

6.4. Reference to other sections

Refer to section 13 for disposal advice.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Avoid all direct contact. Avoid breathing vapours. Wash thoroughly after handling. Utilize exposure controls and personal protection as specified in Section 8. Remove contaminated clothing immediately. Wash clothing before reuse. Contaminated work clothing must not be allowed out of the workplace. Contaminated leather including shoes cannot be decontaminated and should be discarded. When using, do not eat, drink or smoke. Do not contaminate with sodium nitrite or other nitrosating agents, which could cause the formation of cancer-causing nitrosamine. Avoid creating and breathing dust during removal, drilling, grinding, sawing or sanding.

7.2. Conditions for safe storage, including any incompatibilities

Store in a cool, dry and well-ventilated area. Do not store near acids.

7.3. Specific end use(s)

No special precautions.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limit values**

Ingredients	OSHA PEL ¹		ACGIH TLV ²		UK WEL ³		AUSTRALIA ES ⁴	
	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³	ppm	mg/m ³
1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with bisphenol A diglycidyl ether homopolymer	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Diethylenetriamine	1 (Table Z-1-A)	N/A	1 (skin)	4.2	1	4.3	1 (skin)	4.2
Titanium dioxide	(total)	15	N/A	10	(inhal.) (resp.)	10 4	N/A	10
Iron oxide	N/A	10	(resp.)	5	N/A	5 STEL: 10	(fume, as Fe)	5

¹ United States Occupational Health & Safety Administration permissible exposure limits

² American Conference of Governmental Industrial Hygienists threshold limit values

³ EH40 Workplace exposure limits, Health & Safety Executive

⁴ Safe Work Australia, Workplace Exposure Standards for Airborne Contaminants

Biological limit values

No biological exposure limits noted for the ingredient(s).

Derived No Effect Level (DNEL) according to Regulation (EC) No 1907/2006:**Workers**

Substance	Route of exposure	Potential health effects	DNEL
Diethylenetriamine	Inhalation	Acute effects, local	2.6 mg/m ³
		Acute effects, systemic	92.1 mg/m ³
		Chronic effects, local	0.87 mg/m ³
	Dermal	Chronic effects, systemic	15.4 mg/m ³
		Chronic effects, local	1.1 mg/cm ²
Titanium dioxide	Inhalation	Chronic effects, systemic	11.4 mg/kg
		Chronic effects	10 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No 1907/2006:

Substance	Environmental protection target	PNEC
Diethylenetriamine	Fresh water	0.56 mg/l
	Freshwater sediments	1,072 mg/kg
	Marine water	0.056 mg/l
	Marine sediments	107.2 mg/kg
	Microorganisms in sewage treatment	6 mg/l
	Soil (agricultural)	7.97 mg/kg
Titanium dioxide	Fresh water	0.127 mg/l
	Marine water	>= 1 mg/l
	Water	0.61 mg/l
	Freshwater sediments	>= 1000 mg/kg
	Marine sediments	>= 100 mg/kg
	Microorganisms in sewage treatment	>= 100 mg/l
	Soil (agricultural)	100 mg/kg

8.2. Exposure controls**8.2.1. Engineering measures**

Use only in well-ventilated areas. Provide sufficient ventilation to keep the concentrations below the exposure limits. If it is necessary to alter the final cured product such that dust may be generated, use adequate dust extraction or damp down.

8.2.2. Individual protection measures

Respiratory protection: Not normally needed. If exposure limits are exceeded, use a self-contained breathing apparatus (SCBA), supplied air respirator (SAR) or air-purifying respirator (APR) with a suitable filter (e.g., EN filter type A-P2).

Protective gloves: Chemical resistant gloves (e.g., natural rubber, nitrile rubber, neoprene or PVC)

Diethylenetriamine:

Contact type	Glove material	Layer thickness	Breakthrough time*
Full	neoprene	0.65 mm	> 480 min.
Splash	natural rubber	0.6 mm	> 60 min.

*Determined according to EN374 standard.

Eye and face protection: Safety goggles.

Other: Impervious clothing as necessary to prevent skin contact.

8.2.3. Environmental exposure controls

Refer to sections 6 and 12.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Physical state	paste	pH	not applicable
Colour	pink	Kinematic viscosity	48,000 cSt @ 25°C
Odour	strong ammonia odor	Solubility in water	very slight
Odour threshold	not determined	Partition coefficient n-octanol/water (log value)	not applicable
Boiling point or range	not determined	Vapour pressure @ 20°C	not determined
Melting point/freezing point	not determined	Density and/or relative density	1.25 kg/l
% Volatile (by volume)	None	Weight per volume	10.36 lbs/gal.
Flammability	not applicable	Vapour density (air=1)	> 1
Lower/upper flammability or explosion limits	not determined	Rate of evaporation (ether=1)	< 1
Flash point	> 200°C (> 392°F)	% Aromatics by weight	0%
Method	PM Closed Cup	Particle characteristics	not applicable
Autoignition temperature	not determined	Explosive properties	not determined
Decomposition temperature	not determined	Oxidising properties	not determined

9.2. Other information

None

SECTION 10: STABILITY AND REACTIVITY**10.1. Reactivity**

Refer to sections 10.3 and 10.5.

10.2. Chemical stability

Stable

10.3. Possibility of hazardous reactions

No dangerous reactions known under conditions of normal use.

10.4. Conditions to avoid

Open flames and red hot surfaces.

10.5. Incompatible materials

Acids and strong oxidizers like liquid Chlorine and concentrated Oxygen.

10.6. Hazardous decomposition products

Carbon Monoxide, Carbon Dioxide, NOx, Ammonia, amines and other toxic fumes.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 / GHS**

Primary route of exposure under normal use: Inhalation, skin and eye contact.

Acute toxicity -

Oral: Harmful if swallowed. ATE-mix: 680 mg/kg. If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the oesophagus and the stomach.

Substance	Test	Result
1,2-Ethanediamine, N-(2-aminoethyl)-, reaction products with bisphenol A diglycidyl ether homopolymer	LD50, rat	200 (LC0) -500 (LC100) mg/kg
Diethylenetriamine	LD50, rat	1,553 mg/kg
Titanium dioxide	LD50, rat	> 10,000 mg/kg

Dermal: ATE-mix: 4,939 mg/kg.

Substance	Test	Result
Diethylenetriamine	LD50, rabbit	1,045 mg/kg
Titanium dioxide	LD50, rabbit	> 10,000 mg/kg

Inhalation: Vapors can be severely irritating to the eyes and respiratory tract.

Substance	Test	Result
Diethylenetriamine	LC50, rat, 4 h	No mortality at vapor saturation level
Titanium dioxide	LC50, rat, 4 h	> 6.82 mg/l (dust)

Skin corrosion/irritation: Causes burns.

Substance	Test	Result
Diethylenetriamine	Skin irritation, rabbit	Corrosive

Serious eye damage/irritation: Causes serious eye damage.

Substance	Test	Result
Diethylenetriamine	Eye irritation	Corrosive

Respiratory or skin sensitisation: May cause an allergic skin reaction.

Substance	Test	Result
Diethylenetriamine	Skin sensitization, guinea pig	Sensitizing

Germ cell mutagenicity: Diethylenetriamine: this substance was non-mutagenic in a bacterial assay and in a cultured mammalian cell assay.

Carcinogenicity: The International Agency for Research on Cancer (IARC) has designated inhaled titanium dioxide as possibly carcinogenic to humans (group 2B). The titanium dioxide in this product does not separate from the mixture or in of itself become air-borne, therefore it does not present a hazard in normal use.

Reproductive toxicity: Diethylenetriamine: not expected to cause toxicity; effects on or via lactation: data lacking.

STOT – single exposure: May cause respiratory irritation.

STOT – repeated exposure: Diethylenetriamine: based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

11.2. Information on other hazards

None

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. The information given below is based on a knowledge of the components and the ecotoxicology of similar substances.

12.1. Toxicity

Many aquatic species are intolerant to corrosive material such as the unreacted curing agent.

12.2. Persistence and degradability

Diethylenetriamine: expected to be resistant to biodegradation. Unreacted components (Parts A and B), improperly released to the environment, can cause ground and water pollution.

12.3. Bioaccumulative potential

Diethylenetriamine: bioconcentration in aquatic organisms is not expected to be significant (log Kow: -2.13).

12.4. Mobility in soil

Paste. Solubility in water: very slight. In determining environmental mobility, consider the product's physical and chemical properties (see Section 9). Diethylenetriamine: expected to be highly mobile in soil.

12.5. Results of PBT and vPvB assessment

Not available

12.6. Endocrine disrupting properties

None known

12.7. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Combine resin and curative. The final cured material is considered nonhazardous. Landfill sealed containers with stabilized and solidified liquids with a properly licensed facility. May be incinerated at an appropriate facility. Unreacted components are a special waste (classified as hazardous according to 2008/98/EC). Check local, state and national/federal regulations and comply with the most stringent requirement.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number or ID number**

ADG/ADR/RID/ADN/IMDG/I UN2735
CAO:
TDG: UN2735
US DOT: UN2735

14.2. UN proper shipping name

ADG/ADR/RID/ADN/IMDG/I AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 2,2'-IMINODIETHYLAMINE)
CAO:
TDG: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 2,2'-IMINODIETHYLAMINE)
US DOT: AMINES, LIQUID, CORROSIVE, N.O.S. (CONTAINS 2,2'-IMINODIETHYLAMINE)

14.3. Transport hazard class(es)

ADG/ADR/RID/ADN/IMDG/I 8
CAO:
TDG: 8
US DOT: 8

14.4. Packing group

ADG/ADR/RID/ADN/IMDG/I II
CAO:
TDG: II
US DOT: II

14.5. Environmental hazards

NO

14.6. Special precautions for user

NO SPECIAL PRECAUTIONS FOR USER

14.7. Maritime transport in bulk according to IMO instruments

NOT APPLICABLE

14.8. Other information

US DOT: ERG NO. 153
 MAY BE SHIPPED AS LIMITED QUANTITIES IN PACKAGING HAVING A RATED CAPACITY GROSS WEIGHT OF 66 LB. OR LESS
 AND IN INNER PACKAGES NOT OVER 1 LITER (49 CFR 173.154 (B),(1))
IMDG: EMS F-A, S-B, IMDG SEGREGATION GROUP 18-ALKALIS
ADR: CLASSIFICATION CODE C7, TUNNEL RESTRICTION CODE (E)
ADG HAZCHEM CODE : 2X **HIN:** 88/80

SECTION 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU regulations**

Authorisations under Title VII: Not applicable

Restrictions under Title VIII: None

Other EU regulations: Directive 94/33/EC on the protection of young people at work.

15.1.2. National regulations

US EPA SARA TITLE III

312 Hazards:

Chemicals subject to reporting requirements of Section 313 of EPCRA and of 40 CFR 372:

Acute toxicity
Skin corrosion
Serious eye damage
Skin sensitization
Specific target organ toxicity – single exposure

None

TSCA: All components are listed or exempted.

Other national regulations: National implementation of the EC Directive referred to in section 15.1.1.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION

Abbreviations and acronyms: ADG: Australian Dangerous Goods Code
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE: Acute Toxicity Estimate
BCF: Bioconcentration Factor
cATpE: Converted Acute Toxicity point Estimate
CLP: Classification Labelling Packaging Regulation (1272/2008/EC)
ES: Exposure Standard
GHS: Globally Harmonized System
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods
LC50: Lethal Concentration to 50 % of a test population
LD50: Lethal Dose to 50% of a test population
LOEL: Lowest Observed Effect Level
N/A: Not Applicable
NA: Not Available
NOEC: No Observed Effect Concentration
NOEL: No Observed Effect Level
OECD: Organization for Economic Co-operation and Development
PBT: Persistent, Bioaccumulative and Toxic substance
(Q)SAR: Quantitative Structure-Activity Relationship
REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (1907/2006/EC)
REL: Recommended Exposure Limit
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail
SCL: Specific Concentration Limit
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
STOT RE: Specific Target Organ Toxicity, Repeated Exposure
STOT SE: Specific Target Organ Toxicity, Single Exposure
TDG: Transportation of Dangerous Goods (Canada)
TWA: Time Weighted Average
US DOT: United States Department of Transportation
vPvB: very Persistent and very Bioaccumulative substance
WEL: Workplace Exposure Limit
WHMIS: Workplace Hazardous Materials Information System
Other abbreviations and acronyms can be looked up at www.wikipedia.org.

Key literature references and sources for data: Commission des normes, de l'équité, de la santé et de la sécurité du travail (CNESST)
Chemical Classification and Information Database (CCID)
European Chemicals Agency (ECHA) - Information on Chemicals
Hazardous Chemical Information System (HCIS)
National Institute of Technology and Evaluation (NITE)
Swedish Chemicals Agency (KEMI)
U.S. National Library of Medicine Toxicology Data Network (TOXNET)

Procedure used to derive the classification for mixtures according to Regulation (EC) No 1272/2008 [CLP] / GHS:

Classification	Classification procedure
Acute Tox. 4, H302	Calculation method
Skin Corr. 1B, H314	Calculation method
Eye Dam. 1, H318	Calculation method
Skin Sens. 1, H317	Calculation method
STOT SE 3, H335	Bridging principle "Dilution"

Relevant H-statements: H302: Harmful if swallowed.
H312: Harmful in contact with skin.
H314: Causes severe skin burns and eye damage.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H330: Fatal if inhaled.
H335: May cause respiratory irritation.

Hazard pictogram names: Corrosion, exclamation mark

Further information: None

Date of last revision: 11 August 2023

Changes to the SDS in this revision: Sections 1.1, 1.2, 1.3, 2.1, 3.2, 4.1, 4.2, 5.1, 5.2, 5.3, 6.3, 7.2, 8.1, 8.2.1, 8.2.2, 9.1, 11.1, 12.6, 15.1, 16.

This information is based solely on data provided by suppliers of the materials used, not on the mixture itself. No warranty is expressed or implied regarding the suitability of the product for the user's particular purpose. The user must make their own determination as to suitability.